



# **Belinea 10 17 28**

### Best performance for little money

Speed, versatility, elegance and high image quality characterise the new Belinea 10 17 28. With its short response time and good image performance the monitor is ideal for video animations and multimedia applications in the mid-range segment. The new Belinea 10 17 28 is equipped with a TN+Film panel and stands out as a result of its 5 ms response time. We therefore recommend the 17 inch TFT screen for small and mid-sized companies who require a high performance display with good image quality. Good contrast and brightness values as well as integrated speakers combined with the additional DVI-D connection ensure loss-free data transfer and the best image performance especially for graphics and multimedia applications. The Belinea 10 17 27 plays a leading role in this segment, not least as a result of its excellent value for money. The 17 inch TFT display also meets the requirements of private users who require a quick response panel for computer games.

#### **Highlights**

- Response time 5 ms
- Additional DVI-D-Port
- Integrated speakers

## **Application areas**

- Demanding business and multimedia applications
- Small and medium-sized companies
- Multimedia / computer games / videos
- For users for whom strong depiction is as important as an excellent price

















# Belinea 10 17 28 Technical data

Art. No. 111760

Display		Volume (OSD)
Display Type	TFT / Active Matrix	Mute (OSD)
Panel Technology	TN + Film	
Image Size	17 inch	ColourTemperature
Viewable Image Size	43.18 cm	5400K
Picture Size W*H (max.)	338 x 270 mm	6500K
Physical resolution	1280 x 1024 Pixel	9300K
Pixel Pitch	0.264 mm	Supervisor sRGB
Displayable Colours (max.)	16,7 Mio	SNGB
Brightness (typical) Background Lighting	300 cd / sq m 4 CCFLs	Control Settings (external)
Contrast Ratio (typical)	700:1	Brightness (external)
Viewing Angle h/v C/R 10:1	160° / 160°	Contrast (external)
Viewing Angle h/v C/R 5:1	170° / 170°	Automatic Screen Adjust (external)
Coating	Anti Glare	Mute (external)
Response Time: (typical)	5 ms	Menu
Response Time	5 ms	Power
Electrical Data		Maximum Refresh Rates (Resolution D
Horizontal Frequency	31 - 81 kHz	640 * 480
Vertical Frequency	55 - 76 Hz	800 * 600
Video bandwidth (dot rate)	135 MHz	1024 * 768
Rated Voltage	100 - 240 V	1152 * 864
Input Frequency	50 - 60 Hz	1280 * 1024
Power Consumption (ON)	30 W	
Power Consumption (sleep)	1 W	Certifications / Certificates / Standards
Input Signal	digital + analogue	Plug & Play
Audio Amplifier Power Output (2x)	1 W	DDC 1
Late de la constantina della c		DDC 2B
Interfaces Mini D. Sub Connector (15 pin)	No.	DDC-CI Energy Stor
Mini-D-Sub Connector (15 pin)	yes	Energy Star TCO 03
DVI-D (24 pin.) Audio In	yes	TUEV GS
Headphone Connector	yes yes	TUEV GS TUEV Ergonomie
USB Hub (internal)	no	VESA-Standard (Dot Pitch)
555 . ab (internal)	110	Mac compatible
Features		ISO 13406-2
Composite Sync	yes	CE-Marking according to EU-guidelines
Sync On Green	no	3 3 3 3 3
Factory Defined Modes	22 Piece(s)	Accessories
User Defined Modes	16 Piece(s)	DVI-D cable (1,8 m, optional)
OSD	yes	Audio Cable
Speaker (integrated)	yes	Power Cable
Power Adaptor	internal	Pivot Software (optional)
Rotatable through 90°	no	Video Cable (15 pol. Mini D-Sub, Length
Height adjustability	0 mm	
Tilt Back	22 °	Manual(s)
Tilt Forth	2 °	Number of languages in Manual
Swive Left	0°	Measures (net)
Swivel Left Kensington Lock compatible	· · · · · · · · · · · · · · · · · · ·	Width (net)
Kensington Lock compatible Colour	Yes, Case Rear SilverBlackStyle	Height (net)
Coloui	Silver DidCKStyle	Depth (net)
Control Settings (OSD)		Weight (net)
Brightness	yes	
Contrast	yes	Measures (without stand)
Automatic Picture Adjustment	yes	Width (without stand)
ColourTemperature	yes	Height (without stand)
ColourCalibration	yes	Depth (without stand)
Display At Lower Resolutions	full screen	
full screen	yes	Measures (gross)
1:1 Repesentation	no	Weight (gross)
Frequency Display	yes	
Reset	yes	
Video Signal Selection	yes	
OSD Timer	yes	
OSD Position OSD Language(s)	yes Gorman English Einnish	
USD Language(s)	German, English, Finnish, French, Italian, Dutch,	
	Polish, Russian, Spanish	
	i olisti, nussiati, apailisti	

( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( (	
/olume (OSD) /lute (OSD)	yes yes
ColourTemperature	
5400K	no
500K	yes
3300K	yes
Supervisor RGB	yes yes
NOD	y63
Control Settings (external)	
Brightness (external)	yes
Contrast (external) Automatic Screen Adjust (external)	yes
Aute (external)	yes yes
Menu	yes
Power	yes
As the ser Defeate Date (Decel Stee Deceles)	
Maximum Refresh Rates (Resolution Dependent) 440 * 480	75 Hz
00 * 600	75 Hz
024 * 768	75 Hz
152 * 864	75 Hz
280 * 1024	75 Hz
Certifications / Certificates / Standards	
Plug & Play	yes
DDC 1	yes
DDC 2B	yes
DDC-CI	yes
nergy Star	yes
CO 03	yes
TUEV GS	yes
<sup>-</sup> UEV Ergonomie /ESA-Standard (Dot Pitch)	yes 100 x 100 mm
Vac compatible	yes
SO 13406-2	yes
CE-Marking according to EU-guidelines	yes
Accessories	
OVI-D cable (1,8 m, optional)	(Art. Nr. 30 86 91)
Audio Cable	yes
Power Cable	yes
Pivot Software (optional)	no
/ideo Cable (15 pol. Mini D-Sub, Length 1.5 m)	yes
Manual(s)	
lumber of languages in Manual	14
Measures (net)	
Vidth (net)	379 mm
Height (net)	380 mm
Depth (net)	137 mm
Veight (net)	3.8 kg
Measures (without stand)	
Vidth (without stand)	379 mm
Height (without stand)	335 mm
Depth (without stand)	58 mm
Measures (gross)	
Veight (gross)	5.0 kg
veight (gross)	
veignt (gross)	